



IRON STRONG

McWaneDuctile.com

TYTON[®]
JOINT PIPE
3"-36"



McWane Ductile is a division of McWane, Inc.

For Generations


TYTON[®] JOINT PIPE FROM MCWANE DUCTILE

Tyton Joint[®] pipe is manufactured by McWane Ductile in 3" to 36" diameters in standard and pressure classes.

The Tyton Joint was brought to market in the mid-1950s and has been modified periodically ever since. The Tyton Joint is the most widely used gasketing system for pipe in North America and around the world. McWane Ductile's Tyton Joint provides 5 degrees of deflection, allowing easy pipeline routing around obstacles

with a minimal amount of fittings. McWane Ductile offers Tyton Joint pipe with various lining options, including single and double thickness cement, Protecto 401 or bare. Exterior coating options include standard asphaltic paint, zinc or bare. Please contact your local sales representative for more information.

DETAILS & DIMENSIONS



PIPE SIZE IN.	PIPE THICKNESS IN.		OUTSIDE DIAMETER IN.	*DIMENSIONS IN.	
	FROM	TO		A	B
3	.25	.40	3.96	5.80	3.00
4	.25	.41	4.80	7.10	3.15
6	.25	.43	6.90	8.63	3.38
8	.25	.45	9.05	10.94	3.69
10	.26	.47	11.10	13.32	3.75
12	.28	.49	13.20	15.06	3.75
14	.28	.51	15.30	17.80	5.00
16	.30	.52	17.40	19.98	5.00
18	.31	.53	19.50	22.00	5.00
20	.33	.54	21.60	24.12	5.25
24	.33	.56	25.80	28.43	5.50
30	.34	.63	32.00	35.40	6.55
36	.38	.73	38.30	41.84	7.00

*Nominal laying length is 18 ft.

DIMENSIONS AND WEIGHTS FOR SPECIAL CLASSES OF PUSH-ON DUCTILE IRON PIPE

PIPE SIZE IN.	THICKNESS CLASS	NOMINAL THICKNESS IN.	OD* IN.	WT. OF BARREL PER FT.† LB.	TYTON® JOINT		
					WT. OF BELL LB.	WT. PER LGTH.‡ LB.	AVG. WT. PER FT.‡ LB.
3	52	0.28	3.96	9.9	7	185	10.3
3	54	0.34	3.96	11.8	7	220	12.2
3	56	0.40	3.96	13.7	7	255	14.1
4	51	0.26	4.80	11.3	9	210	11.8
4	52	0.29	4.80	12.6	9	235	13.1
4	53	0.32	4.80	13.8	9	255	14.3
4	54	0.35	4.80	15	9	280	15.5
4	56	0.41	4.80	17.3	9	320	17.8
6	50	0.25	6.90	16	11	300	16.6
6	51	0.28	6.90	17.8	11	330	18.4
6	52	0.31	6.90	19.6	11	365	20.2
6	53	0.34	6.90	21.4	11	395	22.0
6	54	0.37	6.90	23.2	11	430	23.8
6	55	0.40	6.90	25	11	460	25.6
6	56	0.43	6.90	26.7	11	490	27.3
8	50	0.27	9.05	22.8	17	425	23.7
8	51	0.30	9.05	25.2	17	470	26.1
8	52	0.33	9.05	27.7	17	515	28.6
8	53	0.36	9.05	30.1	17	560	31.0
8	54	0.39	9.05	32.5	17	600	33.4
8	55	0.42	9.05	34.8	17	645	35.7
8	56	0.45	9.05	37.2	17	685	38.1
10	50	0.29	11.10	30.1	24	565	31.4
10	51	0.32	11.10	33.2	24	620	34.5
10	52	0.35	11.10	36.2	24	675	37.5
10	53	0.38	11.10	39.2	24	730	40.5
10	54	0.41	11.10	42.1	24	780	43.4
10	55	0.44	11.10	45.1	24	835	46.4
10	56	0.47	11.10	48	24	890	49.3
12	50	0.31	13.20	38.4	29	720	40.0
12	51	0.34	13.20	42	29	785	43.6
12	52	0.37	13.20	45.6	29	850	47.2
12	53	0.40	13.20	49.2	29	915	50.8
12	54	0.43	13.20	52.8	29	980	54.4
12	55	0.46	13.20	56.3	29	1040	57.9
12	56	0.49	13.20	59.9	29	1105	61.5
14	50	0.33	15.30	47.5	45	900	50.0
14	51	0.36	15.30	51.7	45	975	54.2
14	52	0.39	15.30	55.9	45	1050	58.4
14	53	0.42	15.30	60.1	45	1125	62.6
14	54	0.45	15.30	64.2	45	1200	66.7
14	55	0.48	15.30	68.4	45	1275	70.9
14	56	0.51	15.30	72.5	45	1350	75.0
16	50	0.34	17.40	55.8	54	1060	58.8
16	51	0.37	17.40	60.6	54	1145	63.6
16	52	0.40	17.40	65.4	54	1230	68.4
16	53	0.43	17.40	70.1	54	1315	73.1
16	54	0.46	17.40	74.9	54	1400	77.9
16	55	0.49	17.40	79.7	54	1490	82.7
16	56	0.52	17.40	84.4	54	1575	87.4
18	50	0.35	19.50	64.4	59	1220	67.7
18	51	0.38	19.50	69.8	59	1315	73.1
18	52	0.41	19.50	75.2	59	1415	78.5
18	53	0.44	19.50	80.6	59	1510	83.9
18	54	0.47	19.50	86	59	1605	89.3
18	55	0.50	19.50	91.3	59	1700	94.6
18	56	0.53	19.50	96.7	59	1800	100.0
20	50	0.36	21.60	73.5	74	1395	77.6
20	51	0.39	21.60	79.5	74	1505	83.6
20	52	0.42	21.60	85.5	74	1615	89.6
20	53	0.45	21.60	91.5	74	1720	95.6
20	54	0.48	21.60	97.5	74	1830	101.6
20	55	0.51	21.60	103.4	74	1935	107.5
20	56	0.54	21.60	109.3	74	2040	113.4
24	50	0.38	25.80	92.9	95	1765	98.2
24	51	0.41	25.80	100.1	95	1895	105.4
24	52	0.44	25.80	107.3	95	2025	112.6
24	53	0.47	25.80	114.4	95	2155	119.7
24	54	0.50	25.80	121.6	95	2385	126.9
24	55	0.53	25.80	128.8	95	2415	134.1
24	56	0.56	25.80	135.9	95	2540	141.2
30	50	0.39	32.00	118.5	139	2270	126.2
30	51	0.43	32.00	130.5	139	2490	138.2
30	52	0.47	32.00	142.5	139	2705	150.2
30	53	0.51	32.00	154.4	139	2920	162.1
30	54	0.55	32.00	166.3	139	3130	174.0
30	55	0.59	32.00	178.2	139	3345	185.9
30	56	0.63	32.00	190.0	139	3560	197.7
36	50	0.43	38.30	156.5	184	3000	166.7
36	51	0.48	38.30	174.5	184	3325	184.7
36	52	0.53	38.30	192.4	184	3645	202.6
36	53	0.58	38.30	210.3	184	3970	220.5
36	54	0.63	38.30	228.1	184	4290	238.3
36	55	0.68	38.30	245.9	184	4610	256.1
36	56	0.73	38.30	263.7	184	4930	273.9


STANDARD DIMENSIONS AND WEIGHTS OF 3" THROUGH 36" PUSH-ON JOINT DUCTILE IRON PIPE

PIPE SIZE IN.	PRESSURE CLASS PSI	NOMINAL THICKNESS IN.	OD* IN.	WT. OF BARREL PER FT.† LB.	TYTON® JOINT		
					WT. OF BELL LB.	WT. PER LGTH.‡ LB.	AVG. WT. PER FT.‡ LB.
3	350	0.25	3.96	8.90	7.00	185	9.20
4	350	0.25	4.80	10.90	9.00	225	11.30
6	350	0.25	6.90	16.00	11.00	300	16.60
8	350	0.25	9.05	21.10	17.00	395	22.00
10	350	0.26	11.10	27.10	24.00	510	28.40
12	350	0.28	13.20	34.80	29.00	655	36.40
14	250	0.28	15.30	40.40	45.00	770	42.90
	300	0.30	15.30	43.30	45.00	825	45.80
	350	0.31	15.30	44.70	45.00	850	47.20
16	250	0.30	17.40	49.30	54.00	940	52.30
	300	0.32	17.40	52.50	54.00	1000	55.50
	350	0.34	17.40	55.80	54.00	1060	58.80
18	250	0.31	19.50	57.20	59.00	1090	60.50
	300	0.34	19.50	62.60	59.00	1185	65.90
	350	0.36	19.50	66.20	59.00	1250	69.50
20	250	0.33	21.60	67.50	74.00	1290	71.60
	300	0.36	21.60	73.50	74.00	1395	77.60
	350	0.38	21.60	77.50	74.00	1470	81.60
24	200	0.33	25.80	80.80	95.00	1550	86.10
	250	0.37	25.80	90.50	95.00	1725	95.80
	300	0.40	25.80	97.70	95.00	1855	103.00
	350	0.43	25.80	104.90	95.00	1985	110.20
30	150	0.34	32.00	103.50	139.00	2000	111.20
	200	0.38	32.00	115.50	139.00	2220	123.20
	250	0.42	32.00	127.50	139.00	2435	135.20
	300	0.45	32.00	136.50	139.00	2595	144.20
36	350	0.49	32.00	148.40	139.00	2810	156.10
	150	0.38	38.30	138.50	184.00	2675	148.70
	200	0.42	38.30	152.90	184.00	2935	163.10
	250	0.47	38.30	170.90	184.00	3260	181.10
36	300	0.51	38.30	185.30	184.00	3520	195.50
	350	0.56	38.30	203.20	184.00	3840	213.40

† Including bell; calculated weight of pipe rounded off to the nearest 5 lb.

‡ Including bell; average weight per foot, based on calculated weight of pipe before rounding.

* Tolerances of OD of spigot end: 3-12 in. = +0.06 in. & -0.06 in.; 14-24 in. = +0.05 in. & -0.08 in.; 30-36 in. = +0.08 in. & -0.06 in.




TYTON® JOINT PIPE MAXIMUM ALLOWABLE JOINT DEFLECTION

PIPE SIZE IN.	Y-MAXIMUM JOINT DEFLECTION IN DEGREES	X DEFLECTION IN INCHES 18 FT. LENGTH	APPROXIMATE RADIUS IN FT. OF CURVE PRODUCED BY SUCCESSION OF JOINTS 18 FT. LENGTH
3	5°	19	206
4	5°	19	206
5	5°	19	206
6	5°	19	206
8	5°	19	206
10	5°	19	206
12	5°	19	206
14	5°	19	206
16	5°	19	206
18	5°	19	206
20	5°	19	206
24	5°	19	206
30	5°	19	206
36	5°	19	206


Note: If using Sure Stop 350® locking gaskets, please refer to the deflection limits for that product.

TYTON JOINT® ASSEMBLY INSTRUCTIONS



STEP 1. Thoroughly clean out the bell with special attention to the gasket recess. Remove any foreign material or excess paint. Clean the spigot or beveled plain end and remove any sharp edges with a standard file.




STEP 2. After making sure that the correct gasket is being used, insert it into the recess in the bell with the small end of the gasket facing the bell face.



STEP 3. Apply lubricant to the inside surface of the gasket, making sure that the entire surface is coated. Apply a generous coating of lubricant to the beveled portion of the plain end.



STEP 4. Guide the plain end into the bell, and while maintaining straight alignment, push the plain end into the bell socket. Once the joint is assembled, necessary deflection can be accomplished.



STANDARDS APPLICABLE TO DUCTILE IRON PIPE AND FITTINGS

THICKNESS DESIGN OF DUCTILE IRON PIPE	ANSI/AWWA C150/A21.50
DUCTILE IRON PIPE FOR WATER AND OTHER LIQUIDS	ANSI/AWWA C151/A21.51, FEDERAL WWP421D, GRADE C
DUCTILE IRON PIPE FOR GRAVITY FLOW SERVICE	ANSI/ASTM A746
DUCTILE IRON FITTINGS FOR WATER AND OTHER LIQUIDS (3 in. through 36 in.)	ANSI/AWWA C110/A21.10
DUCTILE IRON COMPACT FITTINGS (3 in. through 24 in.)	ANSI/AWWA C153/A21.53
FLANGED FITTINGS	ANSI/AWWA C110/A21.10, ANSI B16.1
DUCTILE IRON PIPE WITH THREADED FLANGES	ANSI/AWWA C115/21.15
COATINGS AND LININGS	
Asphaltic	ANSI/AWWA C151/A21.51, ANSI/AWWA C110/A21.10, ANSI/AWWA C153/A21.53
Cement Lining	ANSI/AWWA C104/A21.4
Various Epoxy Linings and Coatings	MANUFACTURER'S STANDARD
Exterior Polyethylene Encasement	ANSI/AWWA C105/A21.5
JOINTS - PIPE AND FITTINGS	
Push-On and Mechanical Rubber-Gasket Joints	ANSI/AWWA C111/A21.11, FEDERAL WWP421D
Flanged	ANSI/AWWA C115/A21.15, ANSI B16.1
Grooved and Shouldered	ANSI/AWWA C606
PIPE THREADS	ANSI B2.1
INSTALLATION	ANSI/AWWA C600

Tyton® and Tyton Joint® are registered trademarks of US Pipe and Foundry.



POCKET ENGINEER

Available for iOS + Android
or online at pe.mcwane.com

CONNECT WITH US ON



NEW JERSEY
183 Sitgreaves St.
Phillipsburg, NJ 08865
908-454-1161

OHIO
2266 S. 6th St.
Coshocton, OH 43812
740-622-6651

UTAH
1401 E. 2000 South
Provo, UT 84606
801-373-6910



CANADA
Suite 1, 55 Frid Street,
Hamilton, Ontario, Canada
L8P 4M3