

RATED WORKING PRESSURE AND MAXIMUM DEPTH OF COVER



For Generations

Pipe Size In.	*Pressure Rating psi	Nominal Thickness In.	Laying Conditions				
			Type 1 Trench	Type 2 Trench	Type 3 Trench	Type 4 Trench	Type 5 Trench
			Maximum depth of cover ‡-ft				
3	350	0.25	78	88	99	100§	100§
4	350	0.25	53	61	69	85	100§
6	350	0.25	26	31	37	47	65
8	350	0.25	16	20	25	34	50
10	350	0.26	11**	15	19	28	45
12	350	0.28	10**	15	19	28	44
14	250	0.28	††	11**	15	23	36
	300	0.30	††	13	17	26	42
	350	0.31	††	14	19	27	44
16	250	0.30	††	11**	15	24	34
	300	0.32	††	13	17	26	39
	350	0.34	††	15	20	28	44
18	250	0.31	††	10**	14	22	31
	300	0.34	††	13	17	26	36
	350	0.36	††	15	19	28	41
20	250	0.33	††	10	14	22	30
	300	0.36	††	13	17	26	35
	350	0.38	††	15	19	28	38
24	200	0.33	††	8**	12	17	25
	250	0.37	††	11	15	20	29
	300	0.40	††	13	17	24	32
	350	0.43	††	15	19	28	37
30	150	0.34	††	--	9	14	22
	200	0.38	††	8**	12	16	24
	250	0.42	††	11	15	19	27
	300	0.45	††	12	16	21	29
	350	0.49	††	15	19	25	33
36	150	0.38	††	--	9	14	21
	200	0.42	††	8**	12	15	23
	250	0.47	††	10	14	18	25
	300	0.51	††	12	16	20	28
	350	0.56	††	15	19	24	32

‡ An allowance for a single H-20 truck with 1.5 impact factor is included for all depths of cover.

§ Calculated maximum depth of cover exceeds 100 ft. (30.5 m).

** Minimum allowable depth of cover is 3 ft. (0.9 m).

†† For pipe 14 in. (350 mm) and larger, consideration should be given to the use of laying conditions other than Type 1.



IRON STRONG

NEW JERSEY

183 Sitgreaves St.
Phillipsburg, NJ 08865
908-454-1161
mcwaneductile.com

OHIO

2266 S. 6th St.
Coshocton, OH 43812
740-622-6651
mcwaneductile.com

UTAH

1401 E 2000 S.
Provo, UT 84603
801-373-6910
mcwaneductile.com



Canada Pipe Company ULC

CANADA

1757 Burlington St. E
Hamilton, ON L8N-3R5
905-547-3251
canadapipe.com

